



CCW-599 Deck Coating Accelerator

DESCRIPTION

CCW-599 Accelerator is designed to speed the cure of Carlisle Deck Coatings. This product is especially useful at temperatures of 40° to 70°F (4° to 21°C), where the cure rate would typically be extended.

TYPICAL USE

CCW-599 Accelerator will reduce the time needed for cure by approximately 50%. The cure time of moisture-cured urethanes is highly dependant on temperature and humidity. Below 40°F (4°C) the cure time may be very long, even with the use of CCW-599 Accelerator. Please be sure that each layer is cured to a firm, rubbery film before proceeding with application of the next coat.

PACKAGING

This product is supplied in 4 ounce cans and 1 gallon cans.

Shelf life 12 months from date of manufacture when stored at 85°F or below.

WARNINGS AND HAZARDS

Uncured epoxy compounds may produce irritations following frequent and prolonged contact with the skin. Before use refer to MSDS for important warnings and safety information. Avoid contact with skin, eyes or clothing. The use of gloves, aprons or other protective devices is recommended. In case of skin contact, wash thoroughly with soap and water. If contact with eyes is made, flush thoroughly with clear water and get medical attention.

USAGE

Add one can to a five gallon pail of material and stir thoroughly. If using gallon cans, measure 4 oz. per five gallons carefully using a clean measuring cup. Mix thoroughly. Avoid drawing air into the coating during stirring.

LIMITATIONS

- Do not use at temperatures at or above 75°F (23°C).
- Do not use in conjunction with CCW-501WA as this product is formulated as a fast-cure system.

LIMITED WARRANTY

CARLISLE COATINGS AND WATERPROOFING INCORPORATED (CARLISLE) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any CARLISLE materials prove to contain manufacturing defects that substantially affect their performance, CARLISLE will, at its option, replace the material or refund the purchase price.

This limited warranty is the only warranty extended by CARLISLE with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. CARLISLE specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of CARLISLE's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the CARLISLE material in question.