



Eco-Fast™ II Base Coat Catalyst

DESCRIPTION

EcoFast II Base Coat Catalyst is designed to speed the cure of EcoFast II Base Coat. This product is especially useful at temperatures of 40° to 70°F (4° to 21°C), where the cure rate would typically be extended.

TYPICAL USE

EcoFast II Base Coat Catalyst will reduce the time needed for cure to approximately 4-5 hours at 77° F, 50% humidity. Be sure that the Base Coat has cured to a firm, rubbery film before proceeding with the next coat. The cure time of moisture-cured urethanes is highly dependant on temperature and humidity. Below 40°F (4°C) the cure time may be longer, even with the use of EcoFast II Base Coat Catalyst. Please be sure that each layer is cured to a firm, rubbery film before proceeding with application of the next coat.

PACKAGING

Supplied in 1 pint cans, 6 cans/ct

Shelf life 12 months from date of manufacture when stored at 85°F or below.

WARNINGS AND HAZARDS

Before use, refer to MSDS for important warnings and safety information. Avoid contact with skin, eyes or clothing. The use of gloves, aprons or other protective devices is recommended. In case of skin contact, wash thoroughly with soap and water. If contact with eyes is made, flush thoroughly with clear water and get medical attention.

USAGE

Add one pint can to a five gallon pail of Ecofast II Base Coat, materials should be thoroughly mixed with a jiffy paddle at low speed (400-600 rpm). Take care not to introduce air into the product.

LIMITATIONS

- Pot life and cure times may be significantly reduced under high-temperature, high-humidity conditions.
- Do not use in conjunction with CCW-501WA, as this product is formulated as a fast-cure system.

LIMITED WARRANTY

Carlisle Coatings and Waterproofing, Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the material or refund the purchase price.

This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.

